

Damage integral and other predictive formulas for nonisothermal heating during laser exposure

Elharith M. Ahmed,^a Gary D. Noojin,^a and Michael L. Denton^{b,*}

^aSAIC, JBSA Fort Sam Houston, Texas, United States

^bAir Force Research Laboratory, JBSA Fort Sam Houston, Texas, United States

Abstract

Significance: Physics-based models supply simulated temperature rises to photothermal damage rate models and provide comprehensive risk assessments for laser-induced damage. As the physics-based models continue to be refined, the damage rate models have not advanced. This peculiar lack of improvement is counterintuitive considering the damage integral (Ω), originally derived for isothermal heating events, and fails to accurately represent the nonisothermal heating from short laser exposures.

Aim: Derive a nonisothermal form of the damage integral and predict more accurately the damage induced by short laser exposures, as well as identify the role of heating rate in laser damage.

Approach: From first principles, we derived a version of the damage integral specific to the shape of thermal profiles rather than the square function provided by Arrhenius plots. We used previously published threshold thermal profiles, where all nonisothermal frequency factors (A_{non}) solved all Ω_{non} values to unity. Nonisothermal correction factors correct isothermal A_{iso} values.

Results: The E_a values were identical for both the isothermal and nonisothermal conventions. Correction factor values for Ω_{iso} ranged from 0.0 (20-s exposures at thermal steady state) to -0.93 (0.05-s exposures). Based on empirical results, we have derived a two-dimensional empirical formula that predicts the heating rate as a function of exposure duration and ambient temperature. Threshold peak temperatures (T_p^{thr}) and threshold critical temperatures are mathematically determined without thermal profiles when appropriate E_a and A_{non} values are established.

Conclusions: We have identified a modified damage integral that does not rely on the Arrhenius plot and provides a value for the frequency factor (A) that accounts for the nonisothermal nature of short laser exposures. The method, validated in our in vitro retinal model, requires thermal profiles recorded under threshold conditions, such as at minimum visible lesions or the boundary of cell death. The method is a new option for laser damage modelers.

© The Authors. Published by SPIE under a Creative Commons Attribution 4.0 International License. Distribution or reproduction of this work in whole or in part requires full attribution of the original publication, including its DOI. [DOI: [10.1117/1.JBO.27.3.035001](https://doi.org/10.1117/1.JBO.27.3.035001)]

Keywords: Arrhenius; photothermal; kinetics; damage integral; damage rate; microthermography.

Paper 210260R received Aug. 23, 2021; accepted for publication Mar. 11, 2022; published online Mar. 31, 2022.

1 Introduction

1.1 History of the Damage Integral (Ω)

In 1947, Henriques and Moritz published a series of systematic studies on the thermal damage kinetics of skin.¹⁻⁴ The authors applied heated water or oil on the surface of human and porcine skin using a special manifold, and looked for redness over a wide range of temperatures (44°C to 60°C) and exposure durations (3 s to 5 h). Their damage results showed an exponential

*Address all correspondence to Michael L. Denton, michael.denton.10@us.af.mil

relationship to temperature and a linear correlation to time, indicating a first order reaction for the “temperature-time history.” Adopting the first order rate law of Arrhenius,⁵ which describes the kinetics of isothermal (constant temperature) chemical reactions, Henriques and Moritz determined their energy of activation (E_a) was similar in value to the energy of denaturation for most purified proteins. To provide a measure of accumulated thermal damage (Ω), Henriques integrated the Arrhenius rate law over time (dt'), using the isothermal peak temperature (T_p) in kelvins, to produce the isothermal damage integral shown as

$$\Omega_{\text{iso}}(\tau) = A_{\text{iso}} \int_0^{\tau} e^{\frac{-E_a}{RT_p}} dt', \quad (1)$$

where A_{iso} is the isothermal frequency factor (s^{-1}), E_a is the activation energy (J mol^{-1}), τ is the thermal exposure duration, and R is the universal gas constant ($8.314 \text{ J mol}^{-1} \text{ K}^{-1}$). With this mathematical representation of damage accumulation, Henriques defined an Ω value of 0.53 to represent reversible epidermal injury, and a value of 1.0 to represent complete necrosis at the basal epidermal layer.⁴ However, the authors noted that the relationship between temperature and time (exposure duration) skewed at the shortest exposures of a few min or less. It is important to note that the authors point out that it took 20 s for the basal epidermal layer to equilibrate thermally to the skin surface.¹ This implies that for all exposure durations, the first 20 s displayed nonisothermal temperature rise, and then isothermal (thermal steady-state) conditions prevailed. At some value for exposure duration, the 20-s nonisothermal temperature rise will become negligible, and the entire exposure can then be approximated as isothermal. This description of early temperature ramp at the site of permanent damage (basal layer of epidermis) would explain the lack of continuity of the damage integral at shorter exposure durations.

The same issue came into play after the invention of the laser,⁶ when research on photothermal damage rate kinetics was accelerated. Laser exposure of absorbing tissue results in a rapid temperature rise that might seem instantaneous, but with proper temporal resolution, a ramp in temperature is evident. The nonisothermal nature of this initial photothermal temperature rise requires relatively long exposure durations to approximate an isothermal condition, just as was the case for Henriques and Moritz. Without an alternative, researchers in the field of laser-tissue interaction adopted the Arrhenius isothermal method described by Henriques decades earlier.

To obtain the Arrhenius rate parameters, A and E_a for calculating Ω values, an accumulated damage level of unity (Ω value = 1.0) is used to indicate the damaged state, and Eq. (1) can be linearized and rearranged to as

$$\text{Ln } \tau = \left(\frac{E_a}{R} \right) \frac{1}{T_p} - \text{Ln } A_{\text{iso}}. \quad (2)$$

To illustrate the nonisothermal nature of short laser exposures we present, as reported in a previous paper,⁷ an averaged thermal profile (temperature versus time) for a 0.25-s exposure at $2 \mu\text{m}$ [Fig. 1(a)], and how that data were used to graph [Fig. 1(b)] Eq. (2). The dashed lines in Fig. 1(a) show the square function of temperature and exposure duration, and the arrow indicates the region of the isothermal assumption that causes an overestimate of the thermal dose delivered to the cells. The shape of the thermal profile dictates the degree of overestimation, and this area decreases as a percentage of the total area with extended exposure duration. From the straight line given by Eq. (2), the slope represents $\frac{E_a}{R}$ and the y-intercept gives $-\text{Ln } A_{\text{iso}}$ [Fig. 1(b)]. Figure 1(a) clearly shows why the Arrhenius integral, with constant temperature assumption, is suited for isothermal conditions, such as enzyme reactions where a small volume of enzyme is added to a reaction mixture that is already thermally equilibrated. Of course, the significance of this overestimation in photothermal damage can only be determined by devising an alternative approach that subtracts this overestimate, which is one purpose of this paper.

Six decades after the invention of the laser, no alternatives have been described that can match the damage prediction capability of the isothermal damage integral. Better methods for measuring and recording temperature responses of biological tissues are now available, such as thermal cameras with reasonable spatial and temporal resolution. Although advancing computational physics models that accurately predict temperature rises based on first principles⁸ is




Fig. 1 Comparing isothermal and nonisothermal heating. (a) Average threshold temperature-rise profiles for a 0.25-s laser exposure (2- μm at 30°C ambient temperature) showing the square function (dashed lines) used to determine the Arrhenius rate parameters (A and E_a). Arrow identifies region of overestimated temperature history used in typical Arrhenius method. Inset to (a) identifies the boundary of cell death, which is the source of the “threshold” thermal profile data. (b) Arrhenius plot to empirically determine A_{iso} ($\text{Exp}[-y\text{-intercept}]$) and E_a (slope $\times R$) using Eq. (2). Dashed arrow shows where the square function of panel (a) falls, as part of the average value on the plot of Eq. (2). Portions of (a) and all of (b) taken from Figs. 5(c) and 5(f) of Ref. 7, respectively. Other thermal profiles used in this study are provided in Fig. 2.

important, by focusing less on empirical measurements to support or refine the quality of damage prediction by the isothermal damage integral, there remains no alternative. Hence, no new data are available that address not only the isothermal, but several other known drawbacks⁹ of the damage integral, including the assumptions that the temperature and exposure duration dependence of the frequency factor are negligible. For a methodical evaluation of the significance of these drawbacks, one needs an experimental system that allows the collection of thermal data that reproducibly generates the same accumulated damage (Ω value), and a nonisothermal mathematical model that eliminates the overestimated portion of the thermal dose. The first requirement was described in a recent publication,⁷ and we will use that previous data to highlight our newly derived nonisothermal model.

To understand the significance of the data previously reported, it is important to understand the term minimum visible lesion, or MVL. The production of a photothermal MVL requires a minimal amount of laser energy to generate the threshold temperature rise leading to damage in a given cell or tissue type. However, due to differences in optical and thermal properties between similar samples, and even within the same sample, delivering the same “threshold” laser irradiance in repeated exposures will likely lead to three types of results; no damage, MVL damage, or damage that extended in size beyond the MVL stage. Thus, the term threshold laser dose, whether irradiance or radiant exposure, is less informative than a threshold temperature history. Only the MVL data are useful because of the desire to assign each exposure an Ω value of 1 for establishing relationships between laser exposure duration and ambient temperature (T_{amb}). This would lead to inefficient data sets. Here, we denote the accumulated thermal history leading to a minimum visible lesion as a threshold thermal dose. A threshold thermal profile defines a threshold thermal dose, as experienced by the tissue during an MVL exposure or equivalent. The threshold thermal dose can be quantified, such as by the Arrhenius integral as a function of the thermal profile (Ω) to arrive at an accumulated damage value. An Ω value of unity ($\Omega = 1$) continues to be used routinely as the amount of accumulated damage barely (threshold) causing death.

1.2 Damage Rate Processes

Laser-induced thermal (photothermal) damage is a complex, multiphasic cellular response to increasing temperature over a specified time. The progression of damage involves thermal transitions (unfolding) of macromolecules, especially proteins, to the point of losing biological function. As the accumulation of nonfunctional biomolecules continues, the ability of the cell to

repair the thermally induced stress diminishes until there is irreversible damage. As shown for whey proteins in solution, the rate of heating can influence the structure and solubility of proteins.^{10,11} Of particular interest is the notion that unfolded proteins have some chance of refolding, unless they begin to aggregate and become irreversibly “denatured.” The reversible protein unfolding process is considered a first-order reaction. deWit and Klarenbeek¹⁰ found that, although their whey protein began to unfold at 70°C for both heating rates of 1°C min⁻¹ and 1°C s⁻¹, the temperature at which the protein started aggregating (also 60% unfolded in both groups) was drastically different. The slower heating rate produced 60% unfolded protein at 73°C, and the faster heating rate produced the 60% unfolded fraction at 85°C. Thus, for temperature rises, there are two kinetic rates (unfolding and aggregation) existing concurrently, depending upon both the peak temperature achieved and the rate of heating.

This example provides kinetics data from slow processes (0.17 to 1°C s⁻¹) relative to the rates of temperature rise produced by laser exposures. For instance, the exposure shown in Fig. 1(a) produced a heating rate of 120°C s⁻¹ (30°C rise in 0.25 s). Considering all the 2- μ m laser heating data from Denton⁷ et al., the range of heating rate in their average threshold thermal profiles was from 7.5°C s⁻¹ (40°C ambient to 55°C peak in the first 2-s of a 20-s exposure) to 800°C s⁻¹ (20°C ambient to 60°C peak in 0.05 s). If we extrapolate the trend described by deWit¹¹ above to the photothermal data, the amount of denatured protein would be low by the end of these short exposures. Perhaps cells are sensitive to a small amount of inactivated protein, especially a protein with a critical function. However, the extremely high protein concentrations within living cells relative to the test tubes of deWit would significantly increase the rate of aggregation of proteins once unfolded.¹² This highlights that, although trends found in test tubes reveal important features for live cells, direct comparisons and interpretations require caution.

2 Methods

2.1 Derivation of Nonisothermal Damage Integral

Due to the complex physical changes in state and chemical aggregation leading to damage, approaching the kinetics as an overall composite system was an alternative starting point to the isothermal chemical reactions of Arrhenius.⁵ The currently accepted kinetic equation for a heterogeneous condensed phase system¹³ is

$$\frac{d\alpha}{dt} = f(\alpha)k(T). \quad (3)$$

The rate of conversion of the measured variable, α , was assumed to equal a separable mass-loss function, $f(\alpha)$, and a temperature dependent rate function, $k(T)$.^{13,14} Think of α as the property of the material that was converted during the temperature dependent process. In laser bio-effects, this would be equivalent to the one or more proteins responsible for cellular damage when denatured. The degree of conversion of α (0.0 to 1.0) that causes cell damage can be arbitrary. Due to the complexity of the cellular components, including our lack of knowledge about the actual protein(s) involved in the damage rate process, α becomes impossible to measure. Therefore, assuming a separable $f(\alpha)$ and $k(T)$ functions, the heterogeneous condensed phase system provides a good starting point. Considering the familiar Arrhenius rate equation to describe the temperature dependent rate function yields

$$k(T) = A_{(\tau)} e^{\frac{-E_a}{RT(t)}}, \quad (4)$$

and substitution into Eq. (3) yields

$$\frac{d\alpha}{dt} = f(\alpha)A_{(\tau)} e^{\frac{-E_a}{RT(t)}}. \quad (5)$$

For variable heating rates, separation of variables and integration of Eq. (5) yields a measure of converted sample ($g(\alpha)$):

$$g(\alpha) = \int_0^\alpha [f(\alpha)]^{-1} d\alpha = A_{(\tau)} \int_0^\tau e^{\frac{-E_a}{RT(t')}} dt'. \quad (6)$$

This formulation was an alternative derivation of the damage integral (Ω) [Eq. (1)] used by Henriques and Moritz and others.^{4,7,15-21} Classically, threshold thermal damage occurs when the integration in Eq. (6), with respect to α , generates a value of one at some time during a nonisothermal insult. The resulting equation is provided as

$$A_{\text{non}} \int_0^\tau e^{\frac{-E_a}{RT(t')}} dt' = \Omega_{\text{non}}(\tau) = 1, \quad (7)$$

where A_{non} and Ω_{non} represent the nonisothermal frequency factor and nonisothermal damage integral, respectively.

Operating Eq. (7) on thermal data shown in Fig. 1(a) entails the region below the line of the profile and represents the nonisothermal heating history. To quantify the region of overestimation shown in Fig. 1(a) (arrow), one can subtract the region under the profile from the region representing the square function (dashed box). To express the isothermal square function as Eq. (8), we replaced $T(t')$ in the exponent of Eq. (7) with peak temperature (T_p), used the bulk time frame of τ , and set the equation equal to 1.0:

$$A_{\text{iso}} e^{\frac{-E_a}{RT_p}} \cdot \tau = 1. \quad (8)$$

We correct for these assumptions using an exposure duration dependent correction factor $\delta_c(\tau)$, that also takes into account the variable heating rate. In essence, we define $\Omega_{\text{non}}(\tau)$ [Eq. (7)] as the false square function [Eq. (8)] minus a correction factor, $\delta_c(\tau)$, as shown in Eq. (9):

$$A_{\text{non}} \int_0^\tau e^{\frac{-E_a}{RT(t')}} dt' = A_{\text{iso}} e^{\frac{-E_a}{RT_p}} \cdot \tau - \delta_c(\tau). \quad (9)$$

However, researchers do not integrate the square function when calculating Ω_{iso} . Instead, modelers predict damage by integrating nonisothermal profiles using the A_{iso} obtained from the isothermal function [Eq. (2), Fig. 1(b)], as depicted in Eq. (10):

$$A_{\text{non}} \int_0^\tau e^{\frac{-E_a}{RT(t')}} dt' = A_{\text{iso}} \int_0^\tau e^{\frac{-E_a}{RT(t')}} dt' - \delta_c(\tau). \quad (10)$$

Because of the fact that E_a is the same value when solved via Eq. (2), rearrangement provides the simplified definition of $\delta_c(\tau)$

$$\delta_c(\tau) = \Omega_{\text{iso}} - \Omega_{\text{non}}. \quad (11)$$

Equation (11) indicates that the correction factor is applicable to the common usage of A_{iso} to determine the damage integral used by the laser research community (Ω_{iso}) and does not correct the entire step function [Eq. (8)]. As such, $\delta_c(\tau)$ is considerably smaller than that if modelers used Eq. (9). Clearly, the correction in Eq. (10) is entirely a function of the frequency factor correction, where A_{iso} is smaller than A_{non} , which consistently leads to an underestimate of damage (Ω_{iso} values $< \Omega_{\text{non}}$) by the modelers. When using threshold thermal profiles, where the value for Ω_{non} is defined as 1, the correction factor simplifies further to $\delta_c(\tau) = \Omega_{\text{iso}} - 1$, reinforcing the fact that the correction factor as defined in Eq. (10) is a negative value.

Upon additional rearrangements, we find the relationship between $\delta_c(\tau)$ and frequency factors, A_{iso} and A_{non} as

$$\delta_c(\tau) = \frac{(A_{\text{iso}} - A_{\text{non}})}{A_{\text{non}}}, \quad (12)$$

and

$$A_{\text{iso}} = A_{\text{non}}(\delta_c(\tau) + 1). \quad (13)$$

Substituting for A_{iso} in Eq. (2) yields

$$\text{Ln } \tau = \left(\frac{E_a}{R}\right) \frac{1}{T_p} - \text{Ln}(A_{\text{non}}(\delta_c(\tau) + 1)), \quad (14)$$

which can be written as

$$\text{Ln } \tau = \left(\frac{E_a}{R}\right) \frac{1}{T_p} - (\text{Ln}(\delta_c(\tau) + 1) + \text{Ln} A_{\text{non}}), \quad (15)$$

where T_p is the peak temperature to be maintained during the exposure to retain the same amount of accumulated thermal damage by the end of exposure. Having a y-intercept with two variables demonstrates that determining A_{non} and $\delta_c(\tau)$ from an Arrhenius plot is impossible. Hence, a different approach must be taken to determine A_{non} and $\delta_c(\tau)$.

2.2 Determination of A_{non} and $\delta_c(\tau)$ Using Individual Threshold Thermal Profiles

As a starting point for determining values for Ω_{non} , we use the simple rearrangement of Eq. (7) to yield

$$A_{\text{non}} = \left[\int_0^\tau e^{\frac{-E_a}{RT(t')}} dt' \right]^{-1}, \quad (16)$$

where $T(t')$ represents $[T_{\text{amb}} + \Delta T(t')]$. Given E_a , this method provides a value for A_{non} from each of our threshold thermal profiles. By means of the Arrhenius plot for each ambient temperature, E_a values are determined from the slope. Using these ambient temperature-dependent E_a values, we calculated mean $A_{\text{non}} \pm$ standard deviations for each set of exposure duration and ambient temperature using Eq. (16). Knowing the value for A_{non} , we can use Eq. (12) to determine $\delta_c(\tau)$ for each threshold thermal profile as well, resulting in mean values of $\delta_c(\tau) \pm$ standard deviations for each set of exposure duration and ambient temperature. Interestingly, one can calculate the A_{iso} value for each thermal profile by the incorrect assumption in Eq. (8) and rearranging it similar to Eq. (16). Therefore, with a relatively small, but significant number of newly generated threshold thermal profiles, one can assess the $\delta_c(\tau)$ [Eq. (13)] needed for correcting previously reported nonthreshold thermal profiles for a given sample type and laser system if desired.

2.3 Source of Threshold Thermal Profiles to Calibrate Nonisothermal Damage Integral

As described in the previous section, once an E_a value for a given T_{amb} is known, individual thermal profiles can provide values for A_{non} using Eq. (16). In contrast to the traditional plotting of Eq. (2) over a series of laser exposure durations, the use of individual thermal profiles enabled the determination of mean A_{non} and A_{iso} values with standard deviations within the same exposure duration. Ideally, “threshold” thermal profiles would be used to determine the Arrhenius rate parameters because then, by definition, the damage integral would solve to a value of unity. We have postulated that, as long as the damage area was smaller than that of the laser footprint, cells at the boundary of damaged and nondamaged cells in exposed cultures should represent the MVL condition [white line in Fig. 1(a), inset].⁷ If this were true, it would open the door for generating threshold thermal profiles using a wide range of laser irradiances and damage areas. Damaged monolayers would provide MVL data without being limited to a small minimum lesion in the center of an exposed area.

Our method for determining the temperature history at the boundaries of damage, termed microthermography,^{7,15} uses high-speed and high-magnification thermal imaging, followed

by an image overlay with postexposure fluorescence images indicating damaged areas. Spatially resolved temperature responses of nonpigmented retinal pigment epithelial (RPE) cells to 2- μm laser irradiation were recorded at 800 fps with an InSb-based camera (ThermoVision SC6000, FLIR Systems, Inc., Boston, Massachusetts), with an effective pixel pitch of about 8 μm at the image plane. Custom LabVIEW image processing routines performed the overlays with the appropriate stretching, resizing, and orientation changes. Once overlaid correctly, our software identified the thermal pixels associated with the boundary by defining a single-pixel region of interest (ROI) around the perimeter of the damaged area [white line in Fig. 1(a), inset]. The final extraction of the thermal history of the boundary ROIs also used the suite of LabVIEW programs. Large damage areas, no $>90\%$ of the laser area, provided a larger number of useful thermal pixels per boundary ROI, which strengthened the statistical power of the method.

We chose 16 different sets of exposure parameters to investigate the relationship between threshold thermal dose of both laser exposure duration and the T_{amb} at which the cells were exposed. We investigated exposure durations of 0.05, 0.25, 1.0, and 20 s, which was much broader than our initial range of 0.1 to 1.0 s.¹⁵ Exposures at the four durations were delivered at four different ambient temperatures. The T_{amb} values chosen were 20°C, 25°C, 30°C, and 40°C. We ensured that the RPE cells were healthy throughout the duration (<15 min) of the experiments when held at these ambient temperatures. Multiple recordings (12 to 20) of thermal responses of cells in real-time with laser exposure provided the thermal data (Fig. 2 and Ref. 7) we used for each of the 16 different combinations of T_{amb} and τ .

In the prior paper, and using the typical isothermal method for determining E_a and A , we verified that, within 10% experimental error, all 16 thermal profiles we extracted from the boundaries of cell death were equivalent to the same Ω value.⁷ Due to the threshold nature of the thermal profiles, we assumed an Ω value of 1.0 for each. Using empirically derived averaged values for A and E_a , each of the 16 average threshold thermal profiles were corrected by scaling the temperature values at each time point by a small increment, until the Ω value solved to 1.0. The scaling factors ranged from 0.6% to 10.3%. Therefore, the thermal profiles from our prior study are equivalent to those from an MVL exposure, allowing us to evaluate differences between isothermal and nonisothermal damage integrals in the current paper.

In preparing the 16 thermal profiles for use in this study, it became apparent that averaging the thermal profiles at each time point to generate one representative thermal profile, as shown in Fig. 2, was not optimum for data analysis. Here, we implemented the more rigorous strategy of a nearest-neighbor interpolation function, which determined numerical expressions of individual profiles. This generated only slight differences to values like T_p , critical temperature (T_{crit}), and E_a relative to the prior data, while providing superior statistical support to our new data. Here, we return to the fundamental aspects of the kinetic rate for a heterogeneous condensed phase system and derive a modified damage integral that removes the overestimated thermal dose. To highlight our results, we used the previously published thermal profiles to compare the differences in E_a and A values associated with nonisothermal treatment relative to the traditional isothermal method. Again, the thermal profiles provided threshold temperature history because they were derived from the boundary of cell death [Fig. 1(a), inset]. As such, we will set the nonisothermal damage integral (Ω_{non}) to unity. The variance from unity found previously for the isothermal damage integral (Ω_{iso}) values provided a measure of error. Another chief outcome of the nonisothermal derivation is that once temperature and exposure duration dependent A and E_a values are obtained for a given sample environment, one can predict threshold T_p (T_p^{thr}) and threshold T_{crit} ($T_{\text{crit}}^{\text{thr}}$) without the need to integrate a thermal profile.

3 Results and Discussion

3.1 Traditional (Isothermal) Convention for Determining Arrhenius Parameters

Traditionally, determining the Arrhenius rate parameters, A_{iso} and E_a , using the Arrhenius plot [Fig. 1(b)] of Eq. (2) requires measuring peak temperatures for multiple laser exposure durations.




Fig. 2 Threshold thermal profiles (temperature rises) for nonpigmented RPE cells exposed at $2\ \mu\text{m}$. Initial 2 s of thermal responses to $2\text{-}\mu\text{m}$ laser exposure at ambient temperatures of (a) 20°C , (b) 25°C , (c) 30°C , and (d) 40°C . Panel (e) provides full thermal profiles for the duration of the 20-s exposures at each of the four ambient temperatures. Temperatures, taken from the boundaries of cell death across a wide range of laser irradiances and damage sizes, are represented as the mean value (with SEM bars) at each time point. Taken from Ref. 7.

This gives one value for each parameter across the entire range of τ values within a given ambient temperature. Table 1 provides the values for A_{iso} and E_a that were determined with an Arrhenius plot using the interpolated thermal profiles from Ref. 7. The laser exposure duration (0.05 ± 0.002 , 0.250 ± 0.002 , 1.000 ± 0.002 , and 20 ± 0.1 s) for each thermal profile was plotted versus the corresponding peak temperature [Eq. (2)]. The linearization of the data generated a single A_{iso} and E_a parameter for each ambient temperature (Table 1). Both A_{iso} and E_a values in Table 1 were greater than the values determined without interpolation.⁷ Differences due to interpolation had little effect (0.4% to 8.7%) on slope (E_a) values. However, due to slight changes in T_p^{thr} values, which propagated into slight changes in y-intercept values, there were large (three to five orders of magnitude) difference in the A_{iso} values between the prior and the current studies. These differences exemplify the large effect on A_{iso} with small changes in the y-intercept when taking the antilog function.

Table 1 Arrhenius rate coefficients from Arrhenius plot.

| Ambient temperature (°C) | From Arrhenius plot | | |
|--------------------------|---------------------|--|--|
| | y-intercept | Arrhenius A_{iso} (s^{-1}) | Arrhenius E_a (J mole^{-1}) |
| 20.2 ± 0.2 | -146.19 | 3.09×10^{63} | 399,161 |
| 24.8 ± 0.2 | -149.93 | 1.30×10^{65} | 410,410 |
| 29.6 ± 0.1 | -189.88 | 2.91×10^{82} | 518,706 |
| 40.0 ± 0.1 | -240.65 | 3.26×10^{104} | 663,627 |

3.2 Nonisothermal Convention for Damage Integral

3.2.1 Correction for nonisothermal damage integral is inherent in A_{non}

The key to subtracting the overestimate in the isothermal square function (Figs. 1 and 2) is applying the nonisothermal correction factor, $\delta_c(\tau)$. However, calculating $\delta_c(\tau)$ using Eq. (12) requires that both A_{non} and the E_a be predetermined. While the E_a values generated by the Arrhenius plot (Table 1) represent both isothermal and nonisothermal heating [Eqs. (2) and (15)], the A_{iso} values represent the isothermal heating. Thermodynamically this makes sense because the threshold peak temperature represents the energy needed to overcome the energy barrier (E_a) of the reaction while the frequency factor (A_{iso}) describes the rate of molecular collisions that results in a reaction. As shown in Fig. 2, T_p^{thr} is the same value in both the thermal profile and the τ versus T_p square function. Therefore, correction of the isothermal to nonisothermal heating rate must come entirely from the frequency factor, which requires a definition different from the value represented by the y-intercept [Eq. (15)].

Values for A_{non} were determined for each threshold thermal profile, not the average thermal profiles, using Eq. (16) and the appropriate E_a value from Table 1. The computed mean values of A_{non} and the standard deviations for each of the four exposure durations within each ambient temperature are listed in Table 2. Similar to how the antilog function causes large variances in A_{iso} data taken from the y-intercepts of Arrhenius plots, the exponential function of Eq. (16) causes large variances in values for A_{non} . To illustrate this wide variance from similar data, we point out that the lines representing averaged thermal profiles in Fig. 2 include standard error of the mean (SEM) error bars (y-axis). Except for the 20-s exposures, the SEM error bars are negligible.

Notice that A_{non} values depend on both T_{amb} and exposure duration. As mentioned in the previous paragraph, the correction for nonisothermal heating must come from the A_{non} values, and the threshold thermal profiles provided this distinction. The general trend within each ambient temperature was for A_{non} to decrease with increasing laser exposure duration. This is because longer exposure times require a lower rate of collisions between molecules for the reaction to take place. As a result, less correction is needed to account for deviation from thermal profiles. The values for A_{non} increase with overall increases in T_{amb} , in a similar manner and magnitude as the A_{iso} values (Table 1).

To calculate individual correction factors, the specific A_{non} values generated by each threshold thermal profile were used, along with the appropriate E_a value, using Eq. (11). Again, we show the resulting $\delta_c(\tau)$ values as means and standard deviations in Table 2. The means and SEM values for the $\delta_c(\tau)$ values within the 0.05, 0.25, 1, and 20 s groups in Table 2 were -0.85 ± 0.08 , -0.58 ± 0.21 , -0.42 ± 0.2 , and 0.006 ± 0.44 , respectively. As expected, there was a strong dependence of $\delta_c(\tau)$ on laser exposure duration. It is interesting to note that for 20-s exposure durations, the $\delta_c(\tau)$ values fluctuated around the zero value. As expected, the size of the correction factor decreases with increase in exposure duration, and it reaches the value of zero at some measure of thermal steady state.

Referring to Eq. (14), the mathematical expression of the y-intercept (within parentheses) reveals a shift in the correction factor before taking the logarithm ($\text{Ln}(A_{\text{non}}(\delta_c(\tau) + 1))$).

Table 2 Important parameters determined empirically or computationally. Data with STDEV values were derived using individual thermal profiles.

| Target ^a T_{amb} (°C) | Target ^a τ (s) | $A_{non} \pm$ STDEV Eq. (16) (s ⁻¹) | A_{iso} (Table 1) (s ⁻¹) | $\Omega_{iso} \pm$ STDEV Eq. (8) | $\delta(\tau) \pm$ STDEV ($\Omega_{iso} - 1$) Eq. (11) | Threshold $T_p \pm$ STDEV (empirical) (°C) | Threshold T_p Eq. (17) (°C) |
|---------------------------------------|-----------------------------------|--|--|--|--|--|-------------------------------------|
| 20 | | | 3.09×10^{63} | | | | |
| | 0.05 | $1.47 \pm 1.85 \times 10^{65}$ | | 0.27 ± 0.33 | -0.73 ± 0.33 | 61.6 ± 4.7 | 62.3 |
| | 0.25 | $1.19 \pm 0.46 \times 10^{64}$ | | 0.34 ± 0.26 | -0.66 ± 0.26 | 59.1 ± 1.2 | 58.6 |
| | 1 | $4.85 \pm 3.03 \times 10^{63}$ | | 0.95 ± 0.61 | -0.05 ± 0.61 | 55.9 ± 1.6 | 55.4 ^b |
| | 20 | $8.89 \pm 8.34 \times 10^{63}$ | | 1.08 ± 1.72 | 0.08 ± 1.72 | 48.7 ± 2.6 | 48.8 |
| 25 | | | 1.30×10^{65} | | | | |
| | 0.05 | $1.66 \pm 1.18 \times 10^{66}$ | | 0.16 ± 0.17 | -0.84 ± 0.17 | 62.7 ± 2.0 | 63 |
| | 0.25 | $6.07 \pm 6.42 \times 10^{65}$ | | 0.36 ± 0.19 | -0.64 ± 0.19 | 59.6 ± 1.5 | 59.3 |
| | 1 | $1.93 \pm 0.89 \times 10^{65}$ | | 0.82 ± 0.39 | -0.18 ± 0.39 | 56.4 ± 1.1 | 56.3 ^b |
| | 20 | $2.21 \pm 1.27 \times 10^{65}$ | | 0.80 ± 0.56 | -0.20 ± 0.56 | 50.0 ± 1.4 | 49.8 |
| 30 | | | 2.91×10^{82} | | | | |
| | 0.05 | $1.32 \pm 2.19 \times 10^{84}$ | | 0.07 ± 0.06 | -0.93 ± 0.06 | 59.5 ± 1.7 | 60.8 |
| | 0.25 | $1.43 \pm 1.42 \times 10^{83}$ | | 0.48 ± 0.62 | -0.52 ± 0.62 | 58.2 ± 1.7 | 58 |
| | 1 | $1.80 \pm 1.60 \times 10^{83}$ | | 0.38 ± 0.34 | -0.62 ± 0.34 | 54.6 ± 1.9 | 55.6 ^b |
| | 20 | $4.99 \pm 2.42 \times 10^{82}$ | | 0.75 ± 0.42 | -0.25 ± 0.42 | 51.1 ± 0.8 | 50.5 |
| 40 | | | 3.26×10^{104} | | | | |
| | 0.05 | $5.72 \pm 4.19 \times 10^{105}$ | | 0.11 ± 0.10 | -0.89 ± 0.10 | 62.6 ± 1.3 | 62.9 |
| | 0.25 | $3.19 \pm 4.06 \times 10^{105}$ | | 0.44 ± 0.65 | -0.56 ± 0.65 | 60.0 ± 1.2 | 60.6 |
| | 1 | $4.57 \pm 3.00 \times 10^{105}$ | | 0.18 ± 0.26 | -0.82 ± 0.26 | 56.5 ± 1.6 | 58.7 ^b |
| | 20 | $2.72 \pm 2.07 \times 10^{104}$ | | 1.40 ± 0.80 | 0.4 ± 0.80 | 56.4 ± 1.3 | 54.6 |

^aExact values for T_{amb} and τ for each thermal profile used when calculating parameters using equations listed.

^bThreshold T_p at 1-s exposure time solves to the threshold critical temperature [see also Eq. (18)].

This necessarily means that the A_{non} is always greater than or equal to the A_{iso} [Eq. (2)], for a negative value of the correction factor. As shown in Table 2, short laser exposure durations, such as those shorter than 1-s in our *in vitro* system, benefit greatly from correction of the damage integral with a nonisothermal frequency factor.

The fact that all the thermal profiles assessed were taken from the boundary of cell death, they meet the requirement for representing threshold events in a manner similar to an MVL.⁷ This is the basis for using these thermal profiles to calibrate the Arrhenius rate parameters. Slight variations in laser output, depth of buffer above the cells, cell cycle susceptibility, and the optical and thermal properties of the cell samples, all contributed to the temperature profile needed to cause cell death at the boundary of cell death. Thus, collectively the individual threshold thermal profiles provide a measure of heterogeneity, most of which was probably biological in nature. For this reason, we have chosen to use each thermal profile individually instead of the averaged thermal profiles. It is also the impetus for assigning a value of 1.0 for Ω_{non} for the derivations and use of the nonisothermal equations (Sec. 2.1).

To compare with the $\Omega_{non} = 1$ values for all T_{amb} and τ combinations, we calculated Ω_{iso} values using the ambient temperature dependent E_a and A_{iso} values given in Table 1.

Table 3 Linear dependence of the average heating rate on ambient temperature.

| Laser exposure duration (s) | Linear equation ^a | | |
|-----------------------------|-----------------------------------|--------------------------|---------------------------------------|
| | y-intercept (°C s ⁻¹) | Slope (s ⁻¹) | Correlation (<i>R</i> ²) |
| 0.05 | 1228.8 | -19.9 | 0.98 |
| 0.25 | 230.7 | -3.69 | 1.00 |
| 1 | 54.4 | -0.96 | 0.99 |
| 20 | 1.9 | -0.03 | 0.97 |

^aDerived from data in Fig. 3(a) at constant exposure duration.

This analysis is identical to the “Opt E_a/A ” data in Table 3 of our prior publication,⁷ except here we are using the individual interpolated thermal profiles instead of the averaged thermal profiles. Table 2 provides the Ω_{iso} values obtained from the “Opt E_a/A method,” along with their differences from Ω_{non} values. By dividing the Ω_{iso} by Ω_{non} (value of 1.0), the differences would be expressed as fractional differences. As shown in Table 2, for most combinations of exposure duration and T_{amb} the calculated Ω_{iso} values are far less from the required value of 1.0 to confirm damage except for the 20-s exposure duration, where the steady state is considered an excellent approximation. Only the first 0.75 s of the 20-s exposure (Fig. 2) was not at, or near thermal steady state, which represents 3.75% of the exposure duration. This is the reason why A_{iso} is an excellent approximation for our 20-s exposures. Subsequently, the Ω_{iso} calculated for the 20-s exposures was closer to a value of 1.0 than any other (Table 2).

Without correcting the A_{iso} to A_{non} using $\delta_c(\tau)$ for the nonisothermal heating rates, most of the Ω_{iso} values calculated from the known MVL thermal profiles would provide modelers erroneous indications for cell damage. Indeed, we concluded in our previous report that there was a propensity for underestimating cell death (Table 3 in Ref. 7). The correction factors given in Table 2 provide quick reference to the trends in erroneous damage estimates relative to T_{amb} and laser exposure duration.

3.2.2 Threshold heating rate is reciprocally related to laser exposure duration

As indicated in previous sections, the frequency factor in a nonisothermal process (A_{non}) changes as a function of temperature. Thus, it is not a constant parameter throughout the exposure duration, and it increases as a function of time and is expected to remain constant when the temperature reaches steady state. The values of A_{non} computed here were mean values for each exposure duration using threshold thermal profiles so they, along with the appropriate E_a values, are suited for calculating damage rates (Arrhenius) and accumulated damage (nonisothermal damage integral) for the laser-induced damage processes in our cell culture model.

Rather than studying the complex relationships between A_{non} and both ambient temperature and laser exposure duration shown in Table 2, a natural extension is to examine the average heating rates ($\beta_{\text{avg}} = \frac{1}{\tau} \int_{T_{\text{amb}}}^{T_{\text{amb}}^{\text{thr}}} dT$). As expected, the heating rate was inversely proportional to both laser exposure duration and ambient temperature. Figure 3(a) shows that the heating rate needed to cause damage (threshold thermal profiles) depended greatly on T_{amb} and laser exposure duration. Average heating rates across T_{amb} (same τ value) were linear (lines not shown). Rather than providing equations for the β_{ave} versus T_{amb} in Fig. 3(a), we summarize the y intercepts and slopes, with correlation coefficients, in Table 3. Both Fig. 3(a) and Table 3 indicate that β_{avg} must necessarily be larger at lower ambient temperatures to obtain the τ -dependent peak temperature for threshold damage. Note that the dependence on T_{amb} (slopes, Table 3) was greatest for the shortest exposure durations.

The average heating rates within the T_{amb} groups [Fig. 3(b)] had a similar power function relationship to laser exposure duration, where each slope (exponent) indicated that β_{avg} is not just inversely proportional but reciprocally related to laser exposure duration ($\beta_{\text{avg}} \propto \tau^{-1}$).




Fig. 3 Threshold average heating rates in RPE cells exposed to 2- μm laser light. (a) Bar graph showing the relationship between both ambient temperature and laser exposure duration with average heating rate. Bars of yellow, gray, orange, and blue represent exposure durations of 0.05, 0.25, 1.0, and 20 s, respectively. (b) Power function trends between average heating rate and exposure duration. Slopes (exponents of power functions) indicate a reciprocal relationship (τ^{-1}) between β_{ave} and τ . Note that $T_{\text{amb}} + \text{prefactor} = T_{\text{crit}}^{\text{thr}}$. All correlation coefficients (R^2) values were unity.

It is interesting to note that this reciprocal relationship extends to all four durations, regardless of whether or not the threshold thermal profile achieved thermal steady state [Fig. 3(b)].

The trends shown in Fig. 3(b) provide more information than just a reciprocal relationship. The prefix values for the power functions, by definition, are the values of β_{avg} at 1 s. When the ambient temperature (Table 1 mean value) was added to the β_{avg} at 1 s, we get our expected critical temperature, $T_{\text{crit}}^{\text{thr}}$ (threshold peak temperature at 1 s). In this way, the $T_{\text{crit}}^{\text{thr}}$ values derived from β_{avg} are 54.8°C, 55.6°C, 54.8°C, and 58.4°C for 20.2°C, 24.8°C, 29.6°C, and 40.0°C ambient temperature (Table 1), respectively. The $T_{\text{crit}}^{\text{thr}}$ values from our β_{avg} analysis from 20°C to 30°C T_{amb} were in line with the values (within the standard deviations) in Table 2 (peak temperature for 1-s exposures). The $T_{\text{crit}}^{\text{thr}}$ value of 58.4°C was only 0.3°C above the standard deviation range for the empirical value in Table 2. This result suggests that if one can empirically determine the $T_{\text{crit}}^{\text{thr}}$ value in any experimental system (cell culture, skin, retina) using threshold thermal profiles determined for 1-s exposures at a given T_{amb} (e.g., body temperature), one can determine the heating rate required for that 1-s exposure, as well as any other exposure durations by applying the reciprocal relationship to τ . More experimental data are needed to confirm this relationship.

3.2.3 Nonisothermal predictive model

Threshold peak temperatures. Methods to compare the predictive consequences of using A_{iso} rather than A_{non} include comparing Ω_{non} (e.g., 1.0) to Ω_{iso} values calculated from either threshold thermal profiles or the values for $\delta_c(\tau) + 1$. As shown in a previous section, the A_{iso} is a valid approximation under steady state conditions only. However, the A_{non} is valid for all exposure durations and is thus applicable to isothermal and nonisothermal heating equally well.

Another metric to examine the validity of correcting for non-isothermal heating rates is the calculation of threshold peak temperatures (T_p^{thr}), which is analogous to the “ T_{TH} ” value derived by Pearce and Thomsen.¹⁹ Table 2 compares differences between empirical threshold T_p values relative to the T_p^{thr} values calculated using A_{non} in the following equation, derived from Eq. (14):

$$T_p^{\text{thr}} = \frac{E_a}{R \text{Ln}(\tau \cdot A_{\text{non}}(\delta_c(\tau) + 1))}. \quad (17)$$

Notice Eq. (17) depends upon the laser exposure duration. The E_a value (energy requirement) drives the damage process to account for the T_{amb} by requiring the proper temperature rise. In addition, the A_{non} values influence T_p^{thr} values due to both T_{amb} and τ trends (Table 2). Similar dependencies are true for calculating the threshold critical temperature (T_{crit}^{thr}), which is Eq. (17) solved with an exposure duration of 1 s, similar to that derived by Pearce and Thomsen.¹⁹ Equation (18) provides the simplified expression for the critical temperature:

$$T_{crit}^{thr} = \frac{E_a}{R \text{Ln}(A_{non}(\delta_c(\tau) + 1))}. \tag{18}$$

Notice how Eqs. (17) and (18) allowed the prediction of these two important threshold temperature values without a thermal profile. Once the proper threshold E_a and A_{non} values are obtained, using a statistically significant number of threshold thermal profiles in a given system, T_p^{thr} and T_{crit}^{thr} values can be predicted for any given laser exposure duration and ambient temperature for that system. At least this seems true in our *in vitro* retinal model.

The closer a damage rate process model can predict T_p^{thr} and T_{crit}^{thr} values relative to empirical values, the more optimal the model. All the T_p^{thr} and T_{crit}^{thr} ($\tau = 1$) reported in Table 2 fall within the standard deviations of the empirical threshold T_p values, also shown in Table 2. This validates the predictive power of Eqs. (17) and (18) that uses A_{non} values. Most importantly, A_{non} not only accurately predicts the T_p^{thr} values, it maintains the required value of unity for Ω_{non} to confirm damage. This is the great advantage of taking the additional work needed to get the A_{non} value.

Average heating rate. For processes carried out at a constant heating rate (β), $= \frac{dT}{dt}$, Eq. (5) can be reorganized to Eq. (19):

$$\frac{d\alpha}{dT} = f(\alpha) \frac{A_{(t')}}{\beta} e^{\frac{-E_a}{RT(t')}}. \tag{19}$$

Notice that assuming constant temperature (isothermal approach), $\beta = 0$, generates an invalid assumption in the kinetic equation, eliminating its usage for analyzing nonisothermal laser-induced damage to tissue. The temperature history at the boundary location of cell death provides an estimate of the average heating rate required for threshold damage, ($\beta_{ave}^{thr}(\tau)$), as a function of exposure duration. As previously indicated, threshold thermal damage is reached by means of a peak temperature and a heating rate together. In a thermal process with a heating rate below threshold, reaching the threshold peak temperature is not likely to result in the anticipated damage. Calculations of the threshold average heating rate for each exposure duration and ambient temperature used all 198 thermal profiles collected at the boundary of the cell death were tabulated (data not shown). Using the empirical data, we established a two-dimensional (2D) fit of the heating rate $\beta(\tau, T_B)$ as a function of T_{amb} and τ at the boundary of the cell death was determined to be

$$\beta(\tau, T_{amb}) = e^{-\left(\frac{\ln(\tau)+0.0284 \cdot T_{amb}-3.8828}{0.93}\right)}. \tag{20}$$

Equation (20) is an empirical formula, but it was not a simple “best-fit” analysis. One can convey the analysis as that being a method by which the complex relationships between β_{ave}^{thr} and T_{amb} and τ , shown in Fig. 3, were iteratively related until the formula shown was found to consistently relate the two variables to the correct value for $\beta(\tau, T_{amb})$.

Figure 4 shows the plots of Eq. (20) for varying laser exposure durations at the same four ambient temperatures shown in Fig. 3(b). Notice the similarities between Figs. 3(b) and 4, which indicates a robustness represented using the empirical data to formulate Eq. (20). When the data points for the 16 exposure types (T_{amb} and exposure durations) were used to obtain power functions in Microsoft Excel [as was done in Fig. 3(b)], we obtained similar equations to those in Fig. 3(b). The equations provided in Fig. 4 indicate the same reciprocal relationship and very similar T_{crit}^{thr} values [Eq. (18)]. This agreement between the empirical heating rates and the best-fit




Fig. 4 Plots of Eq. (20) at 20°C, 25°C, 30°C, and 40°C ambient temperature (solid lines). Calculated data points at 0.05, 0.25, 1.0, and 20 s are related to power functions (insets). The equations for the calculated values are essentially identical to those determined empirically [Fig. 3(b)]. Again, the power functions indicate reciprocity (τ^{-1}) and the $T_{\text{amb}} + \text{prefactor} = T_{\text{crit}}^{\text{thr}}$. All correlation coefficients (R^2) values were unity.

2D function validates the predictability of Eq. (20) in our cell culture system using only the A_{non} and E_a values.

4 Summary and Conclusions

A nonisothermal form of the Arrhenius kinetic rate equation [Eq. (6)] was derived from a heterogeneous condensed phase system. By definition, use of threshold thermal profiles, like those from the boundary of cell death or the central temperature of a minimum visible lesion, to integrate the nonisothermal Arrhenius temperature integral [Eq. (7)] allows setting $\Omega_{\text{non}} = 1$. We determined the nonisothermal frequency factor (A_{non}) for every threshold thermal profile (198) by rearranging Ω_{non} to solve for A_{non} [Eq. (16)], which provided a statistical assessment. Once A_{non} was determined, the correction factor, which removes the overestimate identified in Fig. 1(a), can be determined using each threshold thermal profile as well. The correction factor is useful in identifying how disparate the Ω_{iso} values would be if not corrected (Table 2).

The values for Ω_{iso} reported here are not calculated by integrating the isothermal Arrhenius temperature integral, using the square function [Fig. 1(a)], which would lead to the worst-case scenario. Instead, like commonly done in the field of laser–tissue interaction, we integrated (Ω) thermal profiles using A_{iso} values obtained from Eq. (2) and Fig. 1(b), which averages across exposure durations. Results in Table 2 show the importance of determining A_{non} for the short, nonisothermal laser exposure durations. As noted in prior reports,^{7,15} our data underpin the notion that Ω_{iso} values at exposure durations that do not lead to significant thermal steady state are greatly underestimated. We show that this underestimate is associated with A_{iso} values and the correction factor gives the degree of error.

This underestimate in damage accumulation (Ω) might be of interest to those assessing risk for damage using actual or simulated thermal profiles, taking note of the comparisons available in Table 2. We believe an order of magnitude underestimate for damage accumulation from 0.05-s exposures is significant. Existing data, which used the A_{iso} method, could now be corrected for nonisothermal temperature rise if desired. By returning to the original sample system and collecting a statistically significant number of threshold thermal profiles (e.g., MVL or boundary of cell death), one can calculate the $\delta_c(\tau)$, the A_{non} , and set the Ω_{non} value to unity. The difficulty in taking advantage of this correction is calibrating the sample system using threshold thermal profiles. The ability to measure and extract threshold thermal profiles, defined as having a value of $\Omega_{\text{non}} = 1$ as shown by our group,^{7,15} is demanding, but of paramount importance. These thermal profiles standardize the damage integral via the nonisothermal frequency factor.

In addition to its use in threshold damage assessments, the Ω_{non} value, due to its accuracy, provides an estimate for varying degrees of damage. Currently, the ANSI Z136 standard uses a margin of approximately 10-fold between the empirical irradiance damage threshold in the

nonhuman primate retina, and its minimum permissible exposure (MPE) value for safe use of lasers. Our results, based on thermal data rather than laser irradiance, indicate that a fractional value for Ω_{non} might be used similarly, as a maximum permissible thermal exposure (MPTE). Without the variability in sample absorption, and being a thermal metric rather than a laser dose, the MPTE could be set with less margin than the MPE and still provide a safety buffer for potentially hazardous laser exposures. With current progress in thermal models based on physics first principles, simulation of thermal profiles from exposure to known laser parameters supports the use of the MPTE metric in the future if the method is found to be universal among physical models.

Table 2 also provides evidence that the A_{non} is more dependent upon temperature and exposure duration than previously assumed and reported.¹⁹ This, of course, leads to differences between the Ω_{iso} values and the value of unity for Ω_{non} . The dependencies of A_{non} on T_{amb} and τ are complex. Threshold peak temperature (T_p^{thr}) is also dependent upon both T_{amb} and τ , but without drastic swings in value, like A_{non} . However, damage assessment cannot only use T_p^{thr} because the rate of heating plays a major role in damage as well (time-temperature history). Using our threshold thermal profiles, we determined that the average threshold heating rate (β_{avg}) is linear across ambient temperature (Table 3) and reciprocally related across exposure duration [Fig. 3(b)]. This implies that if the exposure duration is doubled, the required threshold β_{avg} is cut in half. Based on these empirical results, we have derived a 2D empirical formula [Eq. (20)] that predicts the heating rate as a function of exposure duration and ambient temperature. We realize our results and assumptions are limited to our hTERT-RPE1 model. To assess for a broader applicability, we have begun to study different cell types in culture, and even extend to *in vivo* models, such as laser damage on skin.²²

Finally, once the corrected A factor for nonisothermal heating is obtained, we can calculate both T_p^{thr} and $T_{\text{crit}}^{\text{thr}}$ in the same manner as shown by Pearce and Thomsen¹⁹ [Eqs. (17) and (18)]. The advantage to using the A_{non} values in these equations is that one can calculate the threshold temperature rises for the same system that correctly predicts $\Omega_{\text{non}} = 1$, and the precise threshold average heating rate. Combined, these parameters provide a more complete picture of the physical state required to cause threshold damage in our model system.

Disclosures

The authors have no relevant financial interests in this article and no potential conflicts of interest to disclose.

Acknowledgments

The opinions expressed in this document, electronic or otherwise, are solely those of the author(s). They do not represent an endorsement by or the views of the United States Air Force, the Department of Defense, or the United States Government. We thank C. D. Clark, III for valuable discussions and insights on the article. This article was approved for public release (PA# 502ABW-2021-0040). This work was supported by the Air Force Research Laboratory, Airman Systems Directorate, Contract Nos. FA8650-14-D-6519 and FA8650-19-C-6024 (EMA, GDN), and the Air Force Office of Scientific Research, Grants No. 14RH10COR and 19RHCOR067 (MLD).

References

1. F. C. Henriques and A. R. Moritz, "Studies of thermal injury in the conduction of heat to and through skin and the temperatures attained therein: a theoretical and experimental investigation," *Am. J. Pathol.* **23**, 531–549 (1947).
2. A. R. Moritz and F. C. Henriques, "Studies of thermal injury II. The relative importance of time and surface temperature in the causation of cutaneous burns," *Am. J. Pathol.* **23**, 695–720 (1947).

3. A. R. Moritz, "Studies of thermal injury III. The pathology and pathogenesis of cutaneous burns: an experimental study," *Am. J. Pathol.* **23**, 915–934 (1947).
4. F. C. Henriques, "Studies of thermal injury V. The predictability and significance of thermally induced rate processes leading to irreversible epidermal injury," *Arch. Pathol.* **43**, 489–502 (1947).
5. S. A. Arrhenius, "About the speed of reaction in the inversion of cane sugar by acids," *Z. Phys. Chem.* **4**, 226–248 (1889).
6. T. Maiman, "Optical and microwave-optical experiments in ruby," *Phys. Rev. Lett.* **4**, 564–566 (1960).
7. M. L. Denton et al., "Effect of ambient temperature and intracellular pigmentation on photo-thermal damage rate kinetics," *J. Biomed. Opt.* **24**(6), 065002 (2019).
8. L. Irvin et al., "BTEC thermal model," USAF Technical Report AFRL-RH-BR-TR-2008-0006 (2008).
9. K. R. Diller and J. A. Pearce, "Issues in modeling thermal alterations in tissues," *Ann. N.Y. Acad. Sci.* **888**, 153–164 (1999).
10. J. N. deWit and G. Klarenbeek, "Effects of various heat treatments on structure and solubility of whey proteins," *J. Dairy Sci.* **67**, 2701–2710 (1984).
11. J. N. deWit, "Nutritional and functional characteristics of whey proteins in food products," *J. Dairy Sci.* **81**, 597–608 (1998).
12. F. Despa et al., "The relative thermal stability of tissue macromolecules and cellular structure in burn injury," *Burns* **31**(5), 568–577 (2005).
13. S. Vyazovkin and C. A. Wight, "Isothermal and non-isothermal kinetics of thermally stimulated reactions of solids," *Int. Rev. Phys. Chem.* **17**(3), 407–433 (1998).
14. J. H. Flynn, "Thermal analysis kinetics-problems, pitfalls and how to deal with them," *J. Therm. Anal.* **34**(1), 367 (1988).
15. M. L. Denton et al., "Errata: spatially correlated microthermography maps threshold temperature in laser-induced damage," *J. Biomed. Opt.* **20**(7), 079801 (2015).
16. N. Koga, "Ozawa's kinetic method for analyzing thermoanalytical curves," *J. Therm. Anal. Calorim.* **113**, 1527–1541 (2013).
17. R. Birngruber, "Thermal modeling in biological tissues," in *Lasers in Biology and Medicine*, F. Hillenkamp, R. Pratesi, and A. Sacchi, Eds., pp. 77–97, Plenum, New York (1980).
18. X. He and J. C. Bischof, "Quantification of temperature and injury response in thermal therapy and cryosurgery," *Crit. Rev. Biomed. Eng.* **31**(5&6), 355–422 (2003).
19. J. Pearce and S. Thomsen, "Rate process analysis of thermal damage," in *Optical Thermal Response of Laser-Irradiated Tissue*, A. J. Welch and M. J. C. van Gemert, Eds., 2nd ed., pp. 487–549, Plenum, New York (2011).
20. S. L. Jacques, "Ratio of entropy to enthalpy in thermal transitions in biological tissues," *J. Biomed. Opt.* **11**(4), 041108 (2006).
21. N. T. Wright and J. D. Humphrey, "Denaturation of collagen via heating: an irreversible rate process," *Annu. Rev. Biomed. Eng.* **4**, 109–128 (2002).
22. M. P. DeLisi et al., "Computational modeling and damage threshold prediction of continuous-wave and multiple-pulse porcine skin laser exposures at 1070 nm," *J. Laser Appl.* **33**, 022023 (2021).

Biographies of the authors are not available.